

Traffic and Transportation Commission

May 20, 2024

Speed Change Ward 8

IV-A. Applicant: Traffic Services Division
Municipal Code §32-167

Request: Change the speed limit on NW 140 Street between Stan Henaman Jr Drive and N Pennsylvania Avenue from 25 miles per hour (mph) to 35 mph.

<u>Traffic Data:</u>	<u>East/West</u>
Street Name:	NW 140 Street
Street Typology:	Neighborhood
bikewalkokc Designation:	Tier 2 facility (bicycle lane) from Quail Springs Mall ring road to N Kentucky Avenue.
Street Width:	Varies from 65 feet, five lanes including two-way left turn lane, two-way, curbed, undivided to 76 feet, six lanes including left and right turn lanes, two-way, curbed, divided at N Pennsylvania Avenue.
Existing Traffic Controls:	Traffic signal at N Pennsylvania Avenue. Side street stop control on Stan Henaman Jr Drive at NW 140 Street. (NW 140 Street is a public street from N Pennsylvania Avenue to Stan Henaman Jr Drive, which is also a public City street. From Stan Henaman Jr Drive west to the Quail Springs Mall ring road, NW 140 Street is a private driveway.)
Parking Controls:	None posted
Traffic Volumes:	8,194 vehicles per day (vpd) (2024)
Existing Speed Limits:	25 mph (not posted between Stan Henaman Jr Drive and N Pennsylvania Avenue) 35 mph (posted between N May Avenue and Joel McDonald Drive)
50th Percentile Speeds:	31 mph (Stan Henaman Jr Drive to N Pennsylvania Avenue) 34 mph (N May Avenue to Joel McDonald Drive)
85th Percentile Speeds:	36 mph (Stan Henaman Jr Drive to N Pennsylvania Avenue) 38 mph (N May Avenue to Joel McDonald Drive)
OCPD Collision Data: (January 2021 – December 2023)	Five (5) collisions recorded on NW 140 Street between Stan Henaman Jr Drive and N Pennsylvania Avenue in 2021; eight (8) in 2022; and 8 in 2023.

Summary: The Traffic Services Division has submitted a recommendation to increase the speed limit on NW 140 Street between Stan Henaman Jr Drive and N Pennsylvania Avenue from 25 mph to 35 mph. The need to post a speed limit on this roadway came to staff's attention following a recent inquiry from the Oklahoma City Police Department.

To the east of Quail Springs Mall, NW 140 Street varies in cross section from an undivided 65 foot wide roadway having five (5) lanes including a

two-way left turn lane at Stan Henaman Jr Drive to a divided 76 foot wide roadway having six (6) lanes including left and right turn lanes, two-way, curbed, divided at N Pennsylvania Avenue. To the east and west of Quail Springs Mall, NW 140 Street is classified as a neighborhood street in planokc. The speed limit on NW 140 Street to the west of Quail Springs Mall is 35 mph and the de facto speed limit on NW 140 Street to the east of the mall is 25 mph. The intersection of N Pennsylvania Avenue and NW 140 Street is controlled by a traffic signal. Stan Henaman Jr Drive is side-street stop controlled at its intersection with NW 140 Street. To the west of Stan Henaman Jr Drive, NW 140 Street becomes part of the private ring road driveway system around Quail Springs Mall.

Oklahoma City Police Department (OCPD) records show there were 5 collisions on NW 140 Street between Stan Henaman Jr Drive and N Pennsylvania Avenue in 2021; 8 in 2022; and 8 in 2023. The majority of crashes recorded occurred at driveway locations.

Available decision sight distance conditions were assessed on NW 140 Street at N Pennsylvania Avenue and at Stan Henaman Jr Drive. Table I in Section 4.3.2 of Article IV of the Subdivision Regulations of the City of Oklahoma City prescribes a minimum decision sight distance of 385 feet for a roadway with a 35 mph speed limit. The available decision sight distance at all intersections and driveways along NW 140 Street exceeds the City's minimum prescribed decision sight distance requirement based on the requested speed limit. A copy of the City's decision sight distance requirement table is included in this report.

To assess current traffic speed conditions, speed studies were conducted on NW 140 Street between N May Avenue and Joel McDonald Drive, which is on the west side of Quail Springs Mall, and on NW 140 Street between Stan Henaman Jr Drive and N Pennsylvania Avenue on April 9, 2024. The purpose of the studies was to examine driver response (travel speed) to the built environment along NW 140 Street to either side of Quail Springs Mall. The speed studies are included at the end of this report and the 50th and 85th percentile speeds are summarized in the Traffic Data section on the first page of this report. The 50th and 85th percentile speeds are those cumulative speeds which 50 and 85 percent, respectively, of all drivers observed travel at or below.

On August 19, 2013, the Commission approved a request from William J Stewart to change the speed limit on NW 140 Street between N May Avenue and Joel McDonald Drive from 25 mph to 35 mph. This section of NW 140 Street, which is on the west side of Quail Springs Mall, is functionally and structurally identical to the section of NW 140 Street between Stan Henaman Jr Drive and N Pennsylvania Avenue. When studied in 2013, the 85th percentile speed on this section of NW 140 Street was observed to be 37 mph. Since the speed limit increase, the observed 85th percentile speed on this section of NW 140 Street in 2024 was 38 mph.

Analysis:

The Manual on Uniform Traffic Control Devices for Streets and Highways (MUTCD), 11th Edition, as published by the United States Department of

Transportation, Federal Highway Administration, Section 2B.21 Speed Limit Sign, establishes rules and guidance regarding the use and application of speed limit signs. Under the "Guidance" section of 2B.21, subsection 10 offers the following for consideration when establishing a speed limit within a speed zone:

"10 On a freeway, expressway, or rural highway (outside urbanized locations or conditions), the speed limit that is posted within a speed zone should be within 5 mph of the 85th percentile speed of free flowing motor vehicle traffic."

Between Stan Henaman Jr Drive and N Pennsylvania Avenue, the observed 50th percentile speed was 31 mph and the observed 85th percentile speed was 36 mph. The highest observed speed was 47 mph.

Since Oklahoma State Law needs to be considered when evaluating speed limit changes, the portion of the state's statutes governing speed limit changes is provided in the following section. Staff notes that Oklahoma State Statute §47-11-803(E) prohibits speed limit alterations in excess of ten (10) miles per hour. The requested speed limit increase is in conformance with this statute in that the posted speed limit on NW 140 Street to the east of N Pennsylvania Avenue is 25 mph.

At the end of the Commission's March 18, 2013, meeting agenda, staff included an article (reprinted with permission) from the Institute of Transportation Engineers' ITE Journal titled, "A Model for Setting Credible Speed Limits in Urban Areas" by Lynda Bellalite. A review of NW 140 Street using the Bellalite methodology scoring system for determining the credible speed limit is as follows:

NW 140 Street (Stan Henaman Jr Drive to N Pennsylvania Avenue)

- **Number of Lanes = 0 points**
(1 lane = 50 points; 2 or 3 lanes = 25 points; 4 or more lanes = 0 points)
- **Width of the Lateral Visual Clearance = 20 points**
(Less than 180 feet = 40 points; 180 feet to 330 feet = 20 points; 330 feet or more = 0 points)
- **Length of the Homogeneous Zone = 20 points**
(Less than 820 feet = 40 points; 820 feet to 1,640 feet = 20 points; 1,640 feet or more = 0 points)
- **Type of Surroundings = 30 points**
(urban = 30 points; mostly urban = 15 points; transitional = 0 points)
- **Number of Institutional Entrance/Exit Points = 0 points**
(None = 0 points; 1 or 2 = 15 points; 3 or more = 25 points)
- **Percentage of the Street Width with On-Street Parking that is Continuously Occupied = 0 points**
(Less than 10% = 0 points; 10% to 30% = 15 points; 30% or more = 25 points)
- **Pavement Width Available = 0 points**
(Less than 20 feet = 10 points; 20 feet to 39 feet = 5 points; 39 feet or more = 0 points)
- **Number of Commercial Buildings = 40 points**
(none = 0 points; 1 to 4 = 20 points; 4 or more = 40 points)

Cumulative Score = 110 points

<u>Credible Speed Limit Point Range</u>	<u>Credible Speed Limit</u>
More than 170 points	25 mph (40 km/h)
120 to 170 points	31 mph (50 km/h)
80 to 120 points	37 mph (60 km/h)
30 to 80 points	43 mph (70 km/h)

The Bellalite methodology suggests a credible speed limit of at least 37 mph for NW 140 Street. The 37 mph credible speed limit is consistent with the observed 31 mph 50th percentile speed and 36 mph 85th percentile speed.

Analysis Summary: Based on how it is structured and the built environment through which it passes, the Bellalite model suggests a credible speed limit of at least 37 mph for the section of NW 140 Street between Stan Henaman Jr Drive and N Pennsylvania Avenue. The observed 50th and 85th percentile speeds on this section of NW 140 Street were 31 mph and 36 mph, respectively. Presently less than seven (7) percent of observed drivers traveled at or below the de facto 25 mph speed limit.

The observed 50th and 85th percentile speeds on NW 140 Street between N May Avenue and Joel McDonald Drive were 34 mph and 38 mph, respectively. On this section of NW 140 Street, less than 5 percent of observed drivers traveled at or below 25 mph.

Recommendation: Staff recommends changing the speed limit on NW 140 Street between Stan Henaman Jr Drive and N Pennsylvania Avenue to 35 mph.

The recommended 35 mph speed limit is consistent with the credible speed limit predicted using the Bellalite method and the observed 85th percentile speed on NW 140 Street and will set a consistent speed limit on this roadway to both sides of Quail Springs Mall.

On NW 140 Street between N May Avenue and Joel McDonald Drive, where the posted speed limit was raised to 35 mph, the observed 50th percentile is 34 mph and the observed 85th percentile speed is 38 mph.

Field review of available decision sight distance conditions found all intersections and driveways on NW 140 Street will meet the City's decision sight distance criteria based on the requested 35 mph speed limit.

Next Actions: Unless the decision of the Traffic and Transportation Commission is appealed, the Commission's action is final.


Traffic Services Division
SC:sc

§ 32-167. Change of speed limits.





When, as a result of a traffic engineering survey, the Commission determines that the movement of vehicular traffic upon the roadway, intersection, or location so surveyed could be controlled with greater safety to life and property or with greater efficiency in the use of the roadway, intersection or location, if the speed limit were increased or reduced, the Commission shall specify such speed limit in terms of miles per hour, and it shall become effective upon the placing of proper signs and markers giving notice thereof.

(Code 1970, § 34-33; Code 1980 § 32-167)

Limits of recommended speed limit change from 25 mph to 35 mph



Local Traffic Control Map




-  Speed Limits (as depicted)
-  Existing traffic controls (as depicted)
-  Limits of requested speed limit change
-  Quail Springs Mall ring road (private driveway system) and limits ring road driveway connection to NW 140 Street

Commission approved speed limit change from 25 mph to 35 mph August 19, 2013 (Item V-H)

Limits of recommended speed limit change from 25 mph to 35 mph



General Vicinity Traffic Control Map

-  Speed Limits (as depicted)
-  Existing traffic controls (as depicted)
-  Limits of requested speed limit change to 35 mph

City of Oklahoma City Intersection Sight Distance Criteria

Intersection sight distance is the *unobstructed and continuous* visual distance required for a driver to detect an unexpected or otherwise difficult-to-perceive information source or hazard in a roadway environment that may be visually cluttered, recognize the hazard or its threat potential, select an appropriate speed and path and initiate and complete the required safety maneuver safely and efficiently. The sight distance required is based on the posted speed limit. Required sight distances are provided in Table 1 of Section 4.3.2, Article IV of the Subdivision Regulations of the City of Oklahoma City. The definition used is that for decision sight distance as included in “A Policy on Geometric Design of Highways and Streets 2001” as published by the American Association of State and Highway Transportation Officials.

The basic parameters used to field evaluate sight distance are as follows:

Three foot six inch (3'-6") driver eye height. The standard location for measuring driver decision sight distance is at a point ten feet (10') back from the curb line and/or edge of pavement.

Four foot three inch (4'-3") roadway object target height.

Minimum Intersection Sight Distance

<u>Posted Speed (MPH)</u>	<u>Minimum Required (feet/yards)</u>	<u>Desirable (feet/yards)</u>
20	220 / 73	315 / 105
25	235 / 78	315 / 105
30	315 / 105	425 / 142
35	385 / 128	515 / 172
40	490 / 163	660 / 220
45	620 / 207	840 / 280
50	750 / 250	1025 / 342
55	890 / 297	1230 / 410

Spot Speed Study on NW 140 East of Quail Springs Mall

Speed limit: 25 MPH

Date: 4/9/24 10:51 AM to 4/9/24 11:08 AM

Total vehicles recorded in file = 101

Lowest recorded speed = 16

Average speed = 31

Highest recorded speed = 47

10 Mph pace speed = 27 - 36

Percent under pace speed = 8

Percent in pace speed = 76

Percent over pace speed = 14

15th percentile = 28

50th percentile = 31

85th percentile = 36

95th percentile = 38



Speed (mph)	Vehicles Counted	Percent of Total	Cumulative Percentage
16	1	1	1
17	0	0	1
18	0	0	1
19	1	1	2
20	0	0	2
21	0	0	2
22	0	0	2
23	3	3	5
24	1	1	5.9
25	1	1	6.9
26	2	2	8.9
27	1	1	9.9
28	8	7.9	17.8
29	13	12.9	30.7
30	11	10.9	41.6
31	10	9.9	51.5
32	5	5	56.4
33	9	8.9	65.3
34	10	9.9	75.2
35	6	5.9	81.2
36	4	4	85.1
37	7	6.9	92.1
38	3	3	95
39	1	1	96
40	0	0	96
41	2	2	98
42	0	0	98
43	0	0	98
44	1	1	99
45	0	0	99
46	0	0	99
47	1	1	100

7% of drivers observed traveled at or below the de facto 25 mph speed limit.

31 mph observed 50th percentile speed.

81% of drivers observed traveled at or below the requested 35 mph speed limit.

36 mph observed 85th percentile speed.

47 mph highest observed speed.

Spot Speed Study on NW 140 West of Quail Springs Mall

Speed limit: 35 MPH

Date: 4/9/24 10:33 AM to 4/9/24 10:46 AM

Total vehicles recorded in file = 117

Lowest recorded speed = 18

Average speed = 34

Highest recorded speed = 45

10 Mph pace speed = 29 - 38

Percent under pace speed = 12

Percent in pace speed = 73

Percent over pace speed = 13

15th percentile = 29

50th percentile = 35

85th percentile = 38

95th percentile = 42



Speed (mph)	Vehicles Counted	Percent of Total	Cumulative Percentage
18	1	0.9	0.9
19	0	0	0.9
20	0	0	0.9
21	0	0	0.9
22	1	0.9	1.7
23	0	0	1.7
24	1	0.9	2.6
25	2	1.7	4.3
26	1	0.9	5.1
27	2	1.7	6.8
28	7	6	12.8
29	4	3.4	16.2
30	5	4.3	20.5
31	5	4.3	24.8
32	13	11.1	35.9
33	7	6	41.9
34	9	7.7	49.6
35	15	12.8	62.4
36	8	6.8	69.2
37	10	8.5	77.8
38	10	8.5	86.3
39	7	6	92.3
40	2	1.7	94
41	1	0.9	94.9
42	2	1.7	96.6
43	0	0	96.6
44	2	1.7	98.3
45	2	1.7	100

5% of drivers observed traveled at or below 25 mph.

34 mph observed 50th percentile speed.

62% of drivers observed traveled at or below the posted 35 mph speed limit.

38 mph observed 85th percentile speed.

45 mph highest observed speed.



Looking east on NW 140 Street across Stan Henaman Jr Drive. To the west of Stan Henaman Jr Drive, NW 140 Street is a private driveway providing access to the Quail Springs Mall ring road system. At this location, NW 140 Street is a 65 foot wide, five lane (including two-way left turn lane), two-way, curbed, undivided roadway. The traffic signal at N Pennsylvania Avenue, approximately one-quarter mile to the east of Stan Henaman Jr Drive, is visible in the distance.



Looking west on NW 140 Street from the raised center median near N Pennsylvania Avenue. At this location, NW 140 Street is a 76 foot wide, six lane (including dedicated left and right turn lanes), two-way, curbed, divided roadway. The Quail Springs Mall ring road, just over one-quarter mile to the west of N Pennsylvania Avenue, is visible in the distance.

A Model for Setting Credible Speed Limits in Urban Areas

This article presents a new model for setting credible speed limits exclusively in urban areas by setting limits from 25 to 43 mph by increments of 6 mph. The model is based on eight key parameters whose cumulative effects significantly affect the 85th percentile speed.

BY LYNDA BELLALITE, PH.D.

Background

Setting speed limits is essential for ensuring appropriate traffic speeds and, more broadly, for improving road safety. In Quebec, Canada, municipalities are responsible for managing speeds on their road network. Since 2007, the Highway Safety Code permits municipalities to adopt a by-law allowing them to change a speed limit in their road network without obtaining prior approval from the Quebec Ministry of Transport. Several municipalities have thus lowered posted speed limits in their road network, notably on collectors, urban arterial roads, or local streets, or close to parks and schools.

To document the impact of these practices on the driver's behavior, the Quebec Ministry of Transport mandated the Université de Sherbrooke to establish the conditions suitable for different speed limits in urban areas. An unanticipated outcome of this research was the design of a model for setting credible speed limits in urban areas.

The Model

This model for setting speed limits was designed to be a decision-support tool. It was developed to set a credible speed limit according to the roadway features and the roadway environment. Indeed, our research shows that some "natural conditions" are conducive to different speed limits.¹

A credible limit corresponds to the operating speed of the vast majority of drivers (85th percentile speed); this is the speed that drivers consider to be suitable given the roadway features and the roadway environment.

Credible speed limits were established by observing the driver's behavior under different conditions.² For more details, the methodological and statistical aspects were documented in an additional paper.³

Our model allows speed limits to be set from 25 to 43 mph (40 to 70 km/h) by in-

crements of 6 mph (10 km/h). The model is based on eight key parameters, among the 70 parameters in the study, whose cumulative effects showed a significant impact on the operating speed of Quebec drivers in urban areas. In decreasing order of importance, they are the number of lanes, the width of the lateral visual clearance, the length of the homogeneous zone, the number of commercial buildings, the type of surroundings, the number of institutional entrance/exit points, the percentage of the street with on-street parking that is continuously occupied, and the pavement width available. In fact, these parameters explain 84 percent of the variance of the 85th percentile speed, whatever the road hierarchy.⁴

To simplify its use, the model was designed as a point scale. Each parameter is given a score according to decision thresholds. The maximum score for each parameter is the result of statistical analyses (such as hierarchical regressions or discriminant analysis). With regard to the thresholds, they correspond to the interval of values obtained by natural statistical clustering from a sample of 100 experimental sites. Because the parameters have a cumulative effect, the user must simply add the score for each parameter and select the credible limit according to the result obtained.

Despite its simplicity, the model is versatile and it proposes credible speed limits for more than 550 possible combinations, representing as much as urban streets.

Model Parameters

The model has eight key parameters whose cumulative effect has a significant impact on the operating speed of Quebec drivers in urban areas.

Among these eight parameters, the number of lanes is the most important. It characterizes the size of the road, which is an indicator used to establish the road hierarchy. Here, the number of lanes is

related to the width of the roadway. This number includes the lanes for motorized vehicles and lanes reserved for buses or other vehicles such as taxis and bicycles. It also includes the space for on-street parking, even if it is temporarily prohibited on certain arterial roads to facilitate the flow of through traffic during rush hour. The general rule is that the operating speed increases with the number of lanes.

The width of the lateral visual clearance is the second parameter. It is related to the openness of the visual field, which is determined by the presence of buildings lining the street and of which the driver is aware. In fact, drivers have a tendency to accelerate when they perceive that sources of potential conflict are distant from the lane in which they are driving. Inversely, if buildings are closer, drivers will spontaneously decelerate. In other words, the clearer the visual scene, the higher the operating speeds.

The length of the homogeneous zone is the third parameter. It corresponds to the distance along which a street has similar features. These features are associated with various uses (e.g., scholastic, commercial, industrial, residential, recreational), occupation density (low, medium, or high), and the characteristics of the road (such as its width or the presence of a median barrier). As soon as a visible and marked change occurs along the road—such as the reduction from four to two lanes, appearance of a traffic island, transition from a residential zone to an industrial park, or transition between different types of residential zone—the homogeneous zone ends. The general rule is that the longer the homogeneous zone, the higher the operating speeds.

The number of commercial buildings is the fourth parameter. Commercial activity attracts large volumes of traffic such as customer traffic or parking activity, which implies the presence of vulnerable road users of whom drivers are aware. In this case, it is not necessary to consider the types of businesses, the nature of the activity, or the surface area because of the design guidelines for businesses in urban areas. In fact, shopping centers, malls, and big-box stores are often set back from the street. Usually, they have large parking lots with controlled access such that their proximity has little influence on the operating speeds on the adjacent road. By contrast, shopping streets

Parameters	Thresholds	Score
Number of lanes	1	50
	2 or 3	25
	4 or more	0
Width of the lateral visual clearance	less than 180 ft.	40
	180 to 330 ft.	20
	330 ft. or more	0
Length of the homogeneous zone	less than 820 ft.	40
	820 to 1,640 ft.	20
	1,640 ft. or more	0
Type of surroundings	urban	30
	mostly urban	15
	transitional	0
Number of institutional entrance/exit points	none	0
	1 or 2	15
	3 or more	25
Percentage of the street with on-street parking that is continuously occupied	less than 10%	0
	10 to 30%	15
	30% or more	25
Pavement width available	less than 20 ft.	10
	20 to 39 ft.	5
	39 ft. or more	0
Number of commercial buildings	none	0
	1 to 4	20
	4 or more	40
Cumulative score	Credible speed limit	
more than 170 points	25 mph (40 km/h)	
120 to 170 points	31 mph (50 km/h)	
80 to 120 points	37 mph (60 km/h)	
30 to 80 points	43 mph (70 km/h)	

lined with boutiques or local businesses create pedestrian activity in close contact with traffic; drivers are aware of this situation and adjust their speed accordingly.

The type of surroundings is the fifth parameter. It describes the environment around the road. The classification is based on the general appearance of the road section, and takes into consideration the layout and the density of buildings. In general, the operating speed increases going from an urban environment to a transition zone. When applying the model, the user refers to a series of photographs to identify the environment corresponding to the road for which the speed limit is being determined.

The number of institutional entrance/exit points is the sixth parameter. Here,

we include religious and educational institutions, recreational facilities such as parks and municipal pools, and community facilities like community centers. In addition to generating large volumes of traffic, these buildings or facilities imply the presence of vulnerable road users. We have observed that drivers tend to decelerate, notably when approaching schools and colleges, even if their speed remains generally above the permitted speed.

The occupancy rate of on-street parking is the seventh parameter. This rate indicates the percentage of a zone with on-street parking that is continuously occupied. On certain streets, on-street parking is authorized. But this is not sufficient to establish an appropriate speed limit. In

fact, if on-street parking is authorized but vehicles rarely use it, drivers may develop the impression that the roadway is wide and causes higher operating speeds. This is the reason why the occupancy rate for on-street parking that is continuously occupied must be taken into account.

The pavement width available is the last parameter. It is related to the width of the roadway minus the width of cycling lanes, the shoulders, and on-street parking spaces. Besides the number of lanes, the pavement width influences the operating speed. For example, a narrow roadway

less than 20 ft. (6 m) wide is generally associated with low speeds. Inversely, a wide road causes high speeds.

Three parameters are particularly associated with the edges of the road and activities along the road: the on-street parking occupancy rate, the number of institutional entrance/exit points, and the number of businesses. The other parameters are more related to roadway characteristics.

Conditions for Applying the Model

The proposed model for determining speed limits in urban areas requires consistency in its application. Neighboring streets that have similar conditions must have the same speed limits. The posted speed limits must be credible so that drivers do not doubt their relevance. In this regard, the model was designed such that the proposed limit should be the same for roads with similar roadway features and with similar roadway environments.

Furthermore, it is preferable to set a uniform limit for an entire road section or neighborhood where the roadway features and the roadside environment are similar. By doing so, drivers perceive the posted speed limit as being more credible and consistent. Different posted limits along homogeneous zones create confusion and lead to noncompliance with the posted limit.

In addition, the application of the model should not lead to frequent changes of the speed limit along a road section. If a road section is very short—for example, less than 820 ft. (250 m)—it is better to reexamine the limit proposed by the model by considering the posted limits in the adjoining sections. Drivers will have difficulty adjusting their speed if changes in the speed limit are too frequent.

Lastly, the model was designed to propose a credible limit according to the roadway features and the road environment. It is possible that the limit suggested by the model will differ from that expected by the user. It is important to understand that the model is based on respecting the operating speed of the vast majority of drivers (85th percentile speed). If the user chooses a speed limit lower than that proposed, without the presence of accompanying measures like traffic calming or police enforcement, it



Figure 1. Example of a road with a credible limit of 25 mph (40 km/h)



Figure 2. Example of a road with a credible limit of 31 mph (50 km/h)



Figure 3. Example of a road with a credible limit of 37 mph (60 km/h)



Figure 4. Example of a road with a credible limit of 43 mph (70 km/h)

is unlikely that drivers will respect the posted speed limit.

Favorable Conditions for Various Speed Limits

Our study, based on close to 100 experimental sites, allowed the identification of not only the key parameters for operating speeds but also the “natural” conditions that are conducive to speeds from 25 to 43 mph (40 to 70 km/h) by increments of 6 mph (10 km/h).

A limit of 25 mph (40 km/h) is appropriate for roads that are relatively short; that is, roads less than 660 ft. (200 m) long on average and that have one or two lanes. These roads are used for local traffic. The width of the driving lane used by motorized vehicle traffic is reduced, that is less than 20 ft. (6 m) wide, because of the narrowness of the road or intensive use of the roadside. On-street parking is permitted on one or both sides of the street and is continuously occupied by numerous vehicles, which reduces the pavement width available to the flow of traffic. These roads are usually lined by institutions or businesses, which leads not only to pedestrian activity but also to considerable parking activity. In general, the lateral clearance is less than 100 ft. (30 m) wide. Buildings are thus close to the road, which reduces the driver’s visual field. These roads are usually in historic downtown areas where the streets are narrow and the building density is relatively high.

A limit of 31 mph (50 km/h) is appropriate for relatively short roads; that is roads that are less than 980 ft. (300 m) long and have two lanes. The pavement width available is generally around 26 ft. (8 m) wide. On-street parking is permitted on one or both sides of the street but is rarely used, thus it does not reduce the width of the pavement available to the flow of traffic. This type of road is often lined by institutions but rarely by businesses. The lateral clearance visual (including the road) is up to 130 ft. (40 m) wide. These roads are found throughout cities, particularly in primarily residential areas.

A limit of 37 mph (60 km/h) is credible for relatively long roads, about 1,300 ft. (400 m) long on average and with several intersections. They are multi-lane

roads (four or more) and are often city boulevards. The pavement width available is approximately 65 ft. (20 m). On-street parking is often permitted, which reduces the roadway width. These roads are never lined by institutions but frequently by businesses. The lateral visual clearance (including the road) is 280 ft. (85 m) wide on average. These roads are generally associated with collectors or subarterials.

A 43 mph (70 km/h) limit is appropriate for roads with homogeneous zones that are relatively long; that is roads that are 1,640 feet (500 m) on average and rarely have intersections. They have multiple lanes (four or more) and often have a median barrier. The pavement width available is approximately 80 ft. (25 m), and on-street parking is rarely permitted. These roads are not lined by institutions and rarely by businesses. The lateral visual clearance (including the road) is wide, reaching 980 ft. (300 m) on average. The function of these roads is to assure the circulation of through traffic, and they have been designed accordingly. These roads are generally urban arterials connecting various districts in a city.

Advantages and Limits of the Model

Although several models⁵ have been developed that address all road types, including roads outside of cities, a major problem is that their parameters are not exclusive to urban environments. As a result, it is difficult for these models to precisely determine appropriate limits in urban areas. By contrast, the proposed model is specifically adapted to urban areas, and it was designed for setting credible limits by increments of 6 mph (10 km/h). In contrast to other models, which require a prior engineering study or which are based on a subjective evaluation, the proposed model is simple to apply and it consists of precise decision thresholds. Statistical analyses have shown that the model correctly sets appropriate limits in 84 percent of cases.

Certain situations can affect the performance of the model and do not allow it to set a limit corresponding to the observed 85th percentile speed. The model is not able to correctly estimate the limit in the presence of a radius of curvature less than 400 ft. (120 m), a street slope ranging

from 4 percent to 8 percent, or a dead-end. These conditions lead to deviations of 9 mph (15 km/h). Furthermore, during the statistical analyses, these parameters were not significant for explaining the 85th percentile speed. It also should be mentioned that the model is based on the observed speeds of Quebec drivers on a municipal road network where the road design corresponds to North American standards. ■

References

1. Bellalite, L. *Étude des Conditions Optimales Correspondant aux Différentes Limites de Vitesse en Milieu Urbain - Rapport Final*. Sherbrooke: Université de Sherbrooke, Laboratoire de recherche et d’application en aménagement, August 2011.
2. Bellalite, L., M.-L. Bouthot, P.-L. Houle, A. Bélisle, J. Martin, G. Pinglot, and M. Varin. *Étude des Conditions Optimales Correspondant aux Différentes Limites de Vitesse en Milieu Urbain - Recueil des Sites*. Sherbrooke, Université de Sherbrooke, Laboratoire de recherche et d’application en aménagement, August 2009.
3. Bellalite, L. *Conception d’un Modèle de détermination des Limites Crédibles en Milieu Urbain* (article soumis à la revue Recherche Transports Sécurité, August 7, 2012).
4. Bellalite, L. *Étude des Conditions Optimales Correspondant aux Différentes Limites de Vitesse en Milieu Urbain - Analyse des Données*. Sherbrooke, Université de Sherbrooke, Laboratoire de recherche et d’application en aménagement, May 2010.
5. Bruneau, J.-F. and L. Bellalite. *Étude des Conditions Optimales Correspondant aux Différentes Limites de Vitesse en Milieu Urbain - Recension des Écrits 2*. Sherbrooke, Université de Sherbrooke, Laboratoire de recherche et d’application en aménagement, February 2011.



LYNDA BELLALITE,

Ph.D. is a full professor at the Université de Sherbrooke, in the Département de Géomatique Appliquée. For the last twenty years her research has dealt with driver behavior and traffic calming. She has also supervised more than 30 graduate students.